

## Powermax65 Ordering Information

CE certified models for use in countries that require CE, CCC or GOST marks.

### Configurations with hand torches

Power source	Part number	Torch and options
65 amps, 400 V and work lead with hand clamp	087117	H65 (75°) hand torch with 25' (7.6 m) lead
	087118	H65 (75°) hand torch with 50' (15 m) lead
	083281	H65 (75°) hand torch and H65s (15°) hand torch with 25' (7.6 m) leads
	083292	H65 (75°) hand torch and H65s (15°) hand torch with 50' (15 m) leads
	083282	H65 (75°) hand torch with 25' (7.6 m) lead and air filter kit and metal filter cover
	083283	H65 (75°) hand torch with 25' (7.6 m) lead, plasma cutting guide and all-in-one consumable kit
65 amps, 400 V (includes CPC port with selectable voltage ratio) and work lead with hand clamp	083284	H65 (75°) hand torch with 25' (7.6 m) lead
	083285	H65 (75°) hand torch with 50' (15 m) lead

### Configurations with machine torches

Power source	Part number	Torch and options
65 amps, 400 V (includes CPC port with selectable voltage ratio) and work lead with hand clamp	083286	M65 machine torch with 25' (7.6 m) lead and remote on/off pendant
	083287	M65 machine torch with 50' (15 m) lead and remote on/off pendant
	083293	M65 machine torch with 25' (7.6 m) lead

### Custom configurations

To create your own configuration, select a power supply, torch, work cable and other needed components.

#### Power supply options (400 V CE)

Standard power supply	Power supply with CPC port and selectable voltage ratio	Power supply with CPC port, selectable voltage ratio and serial interface port (RS-485)
083235	083268	083269

### Component options

Cable length	Torches				Work cables				Control cables		
	H65	H65s	M65	M65m	Hand clamp	C-style clamp	Magnet	Ring terminal	Remote pendant	CNC spade plug <sup>1</sup>	CNC spade plug <sup>2</sup>
15' (4.5 m)			083254	083259							
25' (7.6 m)	083247	083251	083255	083260	223125	223194	223197	223200	128650	228350	023206
35' (11 m)			083256	083261							
50' (15 m)	083248	083252	083257	083262	223126	223195	223198	223201	128651	228351	023279
75' (23 m)	083249	083253	083258	083263	223127	223196	223199	223202	128652		

<sup>1</sup> For use with automation equipment that requires divided arc voltage.

<sup>2</sup> For use when divided arc voltage is not required.